

CHYEN HUAT HARDWARE SDN BHD

RECTANGULAR HOLLOW
 SPEC: BS EN 10219 / MS EN 10219
 ASTM A 500

SIZE IN & MM	THICKNESS (MM)	UNIT WEIGHT KG/M
1/2 X 1" (12MM X 25MM)	1.0	0.543
	1.2	0.642
3/4 X 1 1/2 (19MM X 38MM)	1.0	0.856
	1.2	1.018
	1.5	1.300
1" X 2" (25MM X 50MM)	1.0	1.140
	1.2	1.358
	1.5	1.752
	1.9	2.149
	2.3	2.435
	3.0	3.068
1" X 3" (25MM X 75MM)	1.5	2.380
	2.3	3.338
	3.0	4.245
1 1/2 X 2 1/2 (38MM X 65MM)	1.2	1.885
	1.5	2.455
	1.9	2.886
	2.3	3.446
	3.0	4.387
1 1/2 X 3" (38MM X 75MM)	1.5	2.706
	1.9	3.184
	2.3	3.807
	3.0	4.858
2" X 3" (50MM X 75MM)	1.5	3.008
	1.9	3.542
	2.3	4.241
	3.0	5.423
	4.0	7.024
	4.5	7.786
	5.0	8.522
	6.0	9.917
2" X 4" (50MM X 100MM)	1.6	3.636
	1.9	4.288
	2.3	5.143
	3.0	6.600
	4.0	8.594
	4.5	9.552
	5.0	10.485
	6.0	12.272
2" X 5" (50MM X 125MM)	2.3	6.046
	3.0	7.778
	4.0	10.164
	4.5	11.319
	5.0	12.447
	6.0	14.627

CHYEN HUAT HARDWARE SDN BHD

2" X 6" (50MM X 150MM)	3.0	8.955
	4.0	11.734
	4.5	13.085
	5.0	14.410
	6.0	16.982
3" X 4" (75MM X 100MM)	2.3	6.046
	3.0	7.778
	4.0	10.164
	4.5	11.319
	5.0	12.447
3" X 5" (75MM X 125MM)	3.0	8.955
	4.0	11.734
	4.5	13.085
	5.0	14.410
	6.0	16.982
3" X 6" (75MM X 150MM)	3.0	10.133
	4.0	13.304
	4.5	14.851
	5.0	16.372
	6.0	19.337
	8.0	24.525
4" X 6" (100MM X 150MM)	9.0	27.066
	3.0	11.310
	4.0	14.874
	4.5	16.617
	5.0	18.335
	6.0	21.692
4" X 8" (100MM X 200MM)	8.0	27.665
	9.0	30.598
	4.0	18.014
	4.5	20.150
	5.0	22.260
6" X 8" (150MM X 200MM)	6.0	26.402
	8.0	33.945
	9.0	37.663
	4.5	23.682
	5.0	26.185
6" X 10" (150MM X 250MM)	6.0	31.112
	8.0	40.225
	9.0	44.728
8" X 12" (200MM X 300MM)	6.0	35.822
	8.0	46.505
	9.0	51.793
8" X 12" (200MM X 300MM)	6.0	45.242
	8.0	59.065
	9.0	65.923

TOLERANCE: THICKNESS: PLUS AND MINUS - 10%