

SQUARE HOLLOW

SPEC: BS EN 10219 / MS EN 10219

ASTM A 500

SIZE IN & MM	THICKNESS (MM)	UNIT WEIGHT KG/M
1/2 X 1/2 (12MM X 12MM)	1.0	0.345
	1.2	0.358
5/8 X 5/8 (16MM X 16MM)	1.0	0.464
	1.2	0.548
3/4 X 3/4 (19MM X 19MM)	1.0	0.559
	1.2	0.661
	1.6	0.853
1" X 1" (25MM X 25MM)	1.0	0.747
	1.2	0.596
	1.5	0.808
	2.3	1.595
1 1/4 X 1 1/4 (32MM X 32MM)	3.0	1.997
	1.0	0.997
	1.2	1.150
	1.5	1.510
1 1/2 X 1 1/2 (38MM X 38MM)	2.3	2.100
	3.0	2.656
	1.0	1.209
	1.2	1.380
	1.5	1.217
2" X 2" (50MM X 50MM)	1.9	2.025
	2.3	2.471
	3.0	3.115
	1.2	1.828
	1.5	2.240
	1.9	2.797
2 1/2 X 2 1/2 (65MM X 65MM)	2.3	3.338
	3.0	4.246
	4.0	5.454
	4.5	6.020
	5.0	6.560
	6.0	7.562
2 1/2 X 2 1/2 (65MM X 65MM)	2.3	4.421
	3.0	5.659
	4.0	7.338
	4.5	8.139
	5.0	8.915
	6.0	10.388

CHYEN HUAT HARDWARE SDN BHD

3" X 3" (75MM X 75MM)	1.9	4.290
	2.3	5.144
	3.0	6.601
	4.0	8.594
	4.5	9.552
	5.0	10.485
	6.0	12.272
3 ¹ / ₂ X 3 ¹ / ₂ (90MM X 90MM)	3.0	8.014
	4.0	10.478
	4.5	11.672
	5.0	12.840
	6.0	15.098
4" X 4" (100MM X 100MM)	2.3	6.949
	3.0	8.956
	4.0	11.734
	4.5	13.085
	5.0	14.410
	6.0	16.982
	6.3	17.734
	8.0	21.817
	9.0	24.080
5" X 5" (125MM X 125MM)	4.0	14.874
	4.5	16.617
	5.0	18.335
	6.0	21.692
	8.0	28.097
	9.0	31.145
6" X 6" (150MM X 150MM)	4.0	18.014
	4.5	20.150
	5.0	22.260
	6.0	26.402
	8.0	34.377
	9.0	38.210
8" X 8" (200MM X 200MM)	5.0	30.110
	6.0	35.822
	8.0	46.937
	9.0	52.340
10" X 10" (250MM X 250MM)	6.0	45.242
	8.0	59.497
	9.0	66.470

TOLERANCE: THICKNESS: PLUS AND MINUS - 10%